

NEOREST® 500H Dual Flush Toilet, 1.0GPF/0.8GPF

FEATURES

- TORNADO FLUSH® siphon jet flushing system, ultra high-efficiency (1.0GPF/3.8LPF and 0.8GPF/3.0LPF).
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Auto open/close lid; auto flush
- Multifunction remote control
- Heated seat with temperature control
- EWATER+
- Adjustable spray position
- WASHLET® with three wash modes (front, rear, soft)
- Oscillating and pulsating comfort washing
- Energy saver timer
- Built-in air purifying system

COMPONENTS

- SN952M - Top Unit
- CT952CUMG - Elongated Bowl Unit
- THU9660 - Water Supply Extension Kit (sold separately)

COLORS/FINISHES

- #01 Cotton
- #12 Sedona Beige

PRODUCT SPECIFICATION

The NEOREST 500H with the TORNADO FLUSH system toilet shall be 1.0GPF/3.8LPF and 0.8 GPF/3.0 LPF. Toilet shall have CEFIONTECT ceramic glaze. Toilet shall be of skirted design, elongated front bowl with auto open and close seat. Toilet shall be **TOTO Model MS952CUMG**_____.



- 1G 1 Gallon per Flush
- EWATER+
- TORNADO FLUSH
- CEFIONTECT

CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.19.2/CSA B45.1, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 # 68
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, and others
- Complies with CA Prop 65 warning requirements



CAL Green

MS952CUMG

NEOREST® 500H Dual Flush Toilet, 1.0GPF/0.8GPF

SPECIFICATIONS

Water Use: 1.0 GPF/3.8 LPF & 0.8 GPF/3.0 LPF
 Flush System: TORNADO FLUSH Siphon Jet
 Water Pressure: Min 7 PSI (0.05MPa) Flowing
 Max 105 PSI (0.75MPa) static
 Water Surface: 8-3/4" x 7-1/14"
 Trap Diameter: 2-1/8" (54 mm)
 Rough In: 12" rough in
 Warning: If there is a base board in the restroom, the center of the floor drain should be a minimum of 12" from the base board.

Trap Seal: 2-1/8" (54 mm)
 Warranty: Three Year Limited (Residential)
 One Year Limited (Commercial)

Material: Bowl: Vitreous china
 Seat and cover: Plastic



Shipping Weight: Top Unit - SN952M 21lbs
 Bowl Unit - CT952CUMG 84lbs

Shipping Dimensions: SN952M - 17-3/4" x 31" x 12"
 CT952CUMG - 16-1/2" x 21-1/2" x 29-1/2"

SPECIFIC Power Rating 120V AC, 60Hz, 1290W
 Power Cord Maximum length: 3.94ft (120cm)
 Water Feature Adjustable Water Flow Rate
 Rear washing: from 9.1 to 14.5 oz/min.
 Soft washing: from 10.8 to 14.5 oz/min.
 Front washing: from 9.5 to 14.5 oz/min.
 Wide front washing: from 11.8 to 14.5 oz/min.
 Temperature of Washing Spray
 Minimum: 86° F/30° C
 Maximum: 104° F/40° C
 Drying Feature Safety Features: Thermal fuse
 Air Temperature:
 High: About 140°F (60°C)
 Low: About 95°F (35°C)
 Capacity of Air: 10.24 ft³/min
 Seat Warming Feature Safety Feature: Thermal fuse
 Surface Temperature:
 Minimum: 82°F (28°C)
 Maximum: 97°F (36°C)
 Seat Heater Capacity: 50W
 Safety Feature: Thermal fuse
 Air Purifying Feature Method: O₂ Deodorizer
 Air Volume: 5.7 ft³/min
 Ambient Temperature Range 32°F (0°C) to 104°F (40°C)
 Size 15-5/16" x 27-5/8" x 20-1/4"
 Weight Net: 100 lbs.

INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.



These dimensions and specifications are subject to change without notice