

NEOREST® RS Dual Flush Toilet, 1.0 GPF / 0.8 GPF

FEATURES

- Sleek, low profile one-piece skirted Smart Bidet Toilet with integrated personal cleansing and comfort features
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- HYBRID ECOLOGY SYSTEM™ utilizes an advanced pressure-independent electric flushing system to deliver exceptionally powerful, optimized performance. Paired with ultra high-efficiency TORNADO FLUSH®, it provides powerful waste removal and enhanced bowl cleaning - 1.0/0.8 GPF (3.8/3.0 LPF)
- Auto flush - with back-up manual flush for power outages
- Universal Height, ADA compliant
- Touchless auto open/close lid
- EWATER+® auto-cleans wand, bowl, and under-seat after every use
- PREMIST® automatically mists the bowl before each use
- Self-cleaning wand cleans itself inside and out before and after every use
- CLEAN RESIN® keeps wand and seat cleaner, more hygienic, and effortless to maintain
- Gentle aerated, warm water, front and rear spray with oscillating and pulsating features
- Adjustable spray position, water temperature, and water pressure
- Instantaneous water heater for continuous warm water and energy savings
- Warm air dryer with five variable temperature settings
- Automatic air deodorizer
- Multifunction pearl white remote control with personalized memory settings for up to 4 users
- Heated seat with temperature control
- Seamless seat design eliminates the gap where dirt collects
- CLEAN LIFT® raises the top unit for effortless cleaning underneath
- Night light illuminates behind the toilet and inside of the bowl
- Automatic and programmable energy saving systems

COMPONENTS

- SN8341M - Top Unit
- CT8551CUMFG - Elongated Bowl Unit

COLORS/FINISHES

- #01 Cotton



1G ONE GALLON PER FLUSH

CEFIONTECT

EWATER+

TORNADO FLUSH

U UNIVERSAL HEIGHT

SD SKIRTED DESIGN

AUTO FLUSH

PRODUCT SPECIFICATION

The NEOREST RS with the HYBRID ECOLOGY SYSTEM™ toilet shall be 1.0 GPF / 0.8 GPF (3.8 LPF / 3.0 LPF). Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall be of skirted design, elongated front bowl with auto open and close seat. Toilet shall be TOTO Model MS8341CUMFG#01.

CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.19.2/ CSA B45.1, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 # 68
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, and others
- ADA Compliant
- Complies with CA Prop 65 warning requirement



CALGreen

MS8341CUMFG

NEOREST® RS Dual Flush Toilet, 1.0 GPF / 0.8 GPF


SPECIFICATIONS

Water Use	1.0 GPF / 0.8 GPF (3.8 LPF / 3.0 LPF)
Flush System	HYBRID ECOLOGY SYSTEM™ with TORNADO FLUSH®
Water Pressure	Min: 7.25 PSI (0.05MPa) Flowing Max: 108.75 PSI (0.75MPa) Static
Water Surface	8-5/8" x 7-1/4"
Trap Diameter	2" (51 mm)
Trap Seal	2-1/8" (54 mm)
Warranty	Three Year Limited (Residential) One Year Limited (Commercial)
Material	Bowl: Vitreous China Seat + Cover: Plastic
Power Rating	AC 120 V, 60 Hz, 1290 W
Power Cord	3.9 ft (1.2m)
Rear Washing	Approx. 0.07- 0.11 gal/min
Soft Washing	Approx. 0.07- 0.11 gal/min
Front Washing	Approx. 0.07- 0.11 gal/min
Washing Spray Temperature	Approx. 86°F - 104°F (30°C - 40°C)
Safety Feature	Temperature Fuse
Drying Feature	Air Temperature: Approx. 95°F - 140°F (35°C - 60°C)
Airflow Volume	8.83 ft3/min
Dryer Safety Feature	Temperature Fuse
Seat Warming Feature	Surface Temperature: Approx. 82°F - 97°F (28°C - 36°C)
Seat Heater Capacity	50 W
Air Purifying Feature	O2 Deodorizer
Air Volume	5.65 ft3/min
Ambient Temperature Range	32°F - 104°F (0°C - 40°C)
Product Size	27-1/8" L x 15-1/4" W x 21-1/2" H
Product Weight	95 lbs
Floor to Seat Height	17-11/16" (449mm)
Shipping Weight	SN8341M: 19.5 lbs CT8551CUMFG: 91 lbs

INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.
- Warning:** If there is a base board in the restroom, the center of the floor drain should be a minimum of 12" from the base board.
- It is highly recommended to use a surge protector to prevent damage in the event of a power surge.
- The following factors may affect IR signal strength and top unit operation: product and remote control location, room size, shape, construction materials, and degree of darkness (color) of ceiling and walls.
- This product is designed and evaluated based on the laws and technical standards of the Territory. Use outside the Territory may compromise safety and performance or violate local laws. Warranty, repairs, and technical support are not available for use outside the Territory.

DIMENSIONS



TOTO®

These dimensions and specifications are subject to change without notice